

PRODUCT INFORMATION SHEET

Self-Adhesive Laminated Wallpaper

Product:	Commercial quality self-adhesive (high-tack) vinyl wallpaper + vinyl satin laminate Intended for use in commercial interiors
Finish:	Smooth satin matt - opaque
Size:	up to 120cm wide x up to 280cm length (3.5m maximum)
Weight:	140gsm + laminate
Fire Rating:	Fire rated to Euro Class EN 13501 - 1, equivalent to B1, M1 and Class 0
Installation:	Self-adhesive, very high-tack, opaque Will adhere to most common wall surfaces. Test application is recommended Walls should be completely dry (3 months for new plaster, paint), flat and smooth Walls should have uniform light colour and smooth finish (standard emulsion paint). Painted wall surfaces that have a texture, such as that resulting from a paint roller, might reduce adhesion. Surfaces treated with additional coatings, such as anti-graffiti or anti-bac, may prevent adhesion. Overlap joint method recommended Refer to Printamural Wallpaper Installation Guide
Wall Primer:	Newly painted wall surfaces should be left to dry for 12 weeks before this material is applied. Test application is recommended
Adhesive:	none required
Maintenance:	This product offers some reasonable resistance to light knocks and scuffs, and is wipeable. If necessary, clean with a mild non-soapy detergent and clean soft cloth or sponge. Do not use polishes, abrasive cleaning agents or solvent based cleaning agents. Always carry out a cleaning trial in an inconspicuous area first, to ensure the cleaning agent is suitable. With care the product will retain its original appearance for 3 – 5 years, depending on the area of use.

For further Information please contact us.

Care Home Murals

T 01827 383194
E info@carehomemurals.co.uk
W www.carehomemurals.co.uk

Copyright Care Home Murals 2021 v5.1