

PRODUCT INFORMATION SHEET

Self-Adhesive Repositionable Wallpaper

Product:	Self-adhesive (low-tack) polyester blend fabric tear-resistant wallpaper Intended for use in commercial interiors
Finish:	Matt with a slight texture - opaque
Size:	up to 120cm wide x up to 280cm length (3.5m maximum)
Weight:	100mic
Fire Rating:	A fire rated version of this material is available (at additional cost)
Installation:	Self-adhesive, low-tack easy to install and re-position Leaves no adhesive residue when removed and is recyclable Will adhere to most common wall surfaces. Test application is recommended Walls should be completely dry (3 months for new plaster, paint), flat and smooth Walls should have uniform light colour and smooth finish (standard emulsion paint). Painted wall surfaces that have a texture, such as that resulting from a paint roller, might reduce adhesion. Surfaces treated with additional coatings, such as anti-graffiti or anti-bac, may prevent adhesion. Overlap joint method or overlap and trim through joint method recommended Refer to Printamural Wallpaper Installation Guide
Wall Primer:	Newly painted wall surfaces should be left to dry for 12 weeks before this material is applied. Test application is recommended
Adhesive:	none required
Maintenance:	This product offers some reasonable resistance to light knocks and scuffs, and is wipeable.
	If necessary, clean with a mild non-soapy detergent and clean soft cloth or sponge. Do not use polishes, abrasive cleaning agents or solvent based cleaning agents. Always carry out a cleaning trial in an inconspicuous area first, to ensure the cleaning agent is suitable.
	With care the product will retain its original appearance for $3 - 5$ years, depending on the area of use.

For further Information please contact us.

Care Home Murals

- T 01827 383194
- E info@carehomemurals.co.uk
- W www.carehomemurals.co.uk

Copyright Care Home Murals 2021 v5.1