

PRODUCT INFORMATION SHEET

Self-Adhesive Laminated Door Print

Product:	Commercial quality self-adhesive (high-tack) vinyl wallpaper + vinyl satin laminate
Finish:	Smooth satin matt - opaque
Size:	up to 120cm wide x up to 280cm length (3.5m maximum)
Weight:	140gsm + laminate
Fire Rating:	Fire rated to Euro Class EN 13501 - 1, equivalent to B1, M1 and Class 0
Installation:	Self-adhesive, very high-tack, opaque Will adhere to most common wall surfaces. Test application is recommended Surfaces should be completely dry, flat and smooth with a uniform light colour and smooth finish (standard emulsion paint). Painted surfaces that have a texture might reduce adhesion. Surfaces treated with additional coatings, such as anti-graffiti or anti-bac, may prevent adhesion. Refer to Printamural Door Print Installation Guide
Wall Primer:	Newly painted wall surfaces should be left to dry for 12 weeks before this material is applied. Test application is recommended
Adhesive:	none required
Maintenance:	This product offers some reasonable resistance to light knocks and scuffs, and is wipeable. If necessary, clean with a mild non-soapy detergent and clean soft cloth or sponge. Do not use polishes, abrasive cleaning agents or solvent based cleaning agents. Always carry out a cleaning trial in an inconspicuous area first, to ensure the cleaning agent is suitable. With care the product will retain its original appearance for 3 – 5 years, depending on the area of use.

For further Information please contact us.

Printamural Limited

T 01283 712171
E info@printamural.com
W www.carehomemurals.co.uk