

PRODUCT INFORMATION SHEET

Self-Adhesive Laminated Wallpaper

- Product:** Commercial quality self-adhesive (high-tack) vinyl wallpaper + vinyl satin laminate
Intended for use in commercial interiors
- Finish:** Smooth satin matt - opaque
- Size:** up to 120cm wide x up to 280cm length (3.5m maximum)
- Weight:** 140gsm + laminate
- Fire Rating:** Fire rated to Euro Class EN 13501 - 1, equivalent to B1, M1 and Class 0
- Installation:** Self-adhesive, very high-tack, opaque
Will adhere to most common wall surfaces. Test application is recommended
Walls should be completely dry (3 months for new plaster, paint), flat and smooth
Walls should have uniform light colour and smooth finish (standard emulsion paint).
Painted wall surfaces that have a texture, such as that resulting from a paint roller,
might reduce adhesion.
Surfaces treated with additional coatings, such as anti-graffiti or anti-bac, may prevent
adhesion.
Overlap joint method recommended

Refer to Printamural Wallpaper Installation Guide
- Wall Primer:** Newly painted wall surfaces should be left to dry for 12 weeks before this material is
applied. Test application is recommended
- Adhesive:** none required
- Maintenance:** This product offers some reasonable resistance to light knocks and scuffs, and is
wipeable.

If necessary, clean with a mild non-soapy detergent and clean soft cloth or sponge.
Do not use polishes, abrasive cleaning agents or solvent based cleaning agents.
Always carry out a cleaning trial in an inconspicuous area first, to ensure the cleaning
agent is suitable.

With care the product will retain its original appearance for 3 – 5 years, depending on
the area of use.

For further Information please contact us.

Printamural Limited

T 01283 712171
E info@printamural.com
W www.carehomemurals.co.uk