

## PRODUCT INFORMATION SHEET

**Traditional Wallpaper    Smooth Surface and Linen Texture**

Product:	Commercial quality fabric backed wallpaper, non-woven polyester backing Intended for use in commercial interiors Contains anti fungal/bacteria biocide
Finish	'Linen Texture' or 'Smooth Semi Matt' - opaque
Size:	up to 120cm wide x up to 280cm length (3.5m maximum)
Weight:	410gsm
Fire Rating:	Fully fire rated for commercial interiors to EN 13501-1 B-s2-d0 Class 0 and Class 1 to BS476 part 7 when adhered to a suitable substrate
Installation:	This is a 'paste the wall' product. Will adhere to most common surfaces. Test application is recommended Walls should be dry, flat and smooth - wall blemishes will show Walls should have uniform light colour emulsion or eggshell finish 'Overlap and trim through' joint method recommended Refer to Printamural Wallpaper Installation Guide
Wall Primer:	PVA Primer is recommended.
Adhesive:	For normal pre-emulsified, dry interior walls; Pre-mixed 'Paste the Wall' type water based adhesive suitable for heavy weight fabric backed vinyl wallpapers. Recommended adhesive: Muarspec Murabond Heavy
Maintenance:	This product offers some reasonable resistance to light knocks and scuffs and is wipeable.  If necessary, wipe clean with a mild non-soapy detergent and clean soft cloth or sponge. Do not use polishes, abrasive cleaning agents or solvent based cleaning agents. Always carry out a cleaning trial in an inconspicuous area first, to ensure the cleaning agent is suitable.  With care the product will retain its original appearance for 3 – 5 years, depending on the area of use.

For further Information please contact us.

**Printamural Limited**

T 01283 712171  
E [info@printamural.com](mailto:info@printamural.com)  
W [www.carehomemurals.co.uk](http://www.carehomemurals.co.uk)